- (ii) Surface contamination of strontium-90 on the device of more than 2,200 disintegrations per minute per 100 square centimeters of surface area; or
- (iii) Any other evidence of physical damage.
- (g) The device has been registered in the Sealed Source and Device Registry.

[30 FR 9905, Aug. 10, 1965, as amended at 43 FR 6923, Feb. 17, 1978; 56 FR 23472, May 21, 1991; 58 FR 67660, Dec. 22, 1993; 77 FR 43694, July 25, 2012]

§ 32.62 Same: Quality assurance; prohibition of transfer.

- (a) Each person licensed under §32.61 shall visually inspect each device and shall reject any which has an observable physical defect that could affect containment of the strontium-90.
- (b) Each person licensed under §32.61 shall test each device for possible loss of strontium-90 or for contamination by wiping with filter paper an area of at least 100 square centimeters on the outside surface of the device, or by wiping the entire surface area if it is less than 100 square centimeters. The detection on the filter paper of more than 2,200 disintegrations per minute of radioactive material per 100 square centimeters of surface wiped shall be cause for rejection of the tested device.
- (c) Each person licensed under §32.61 shall:
- (1) Maintain quality assurance systems in the manufacture of the ice detection device containing strontium-90 in a manner sufficient to provide reasonable assurance that the safety-related components of the distributed devices are capable of performing their intended functions; and
- (2) Subject inspection lots to acceptance sampling procedures, by procedures specified in paragraph (d) of this section and in the license issued under §32.61, to provide at least 95 percent confidence that the Lot Tolerance Percent Defective of 5.0 percent will not be exceeded.
- (d) Each person licensed under §32.61 shall subject each inspection lot to:
- (1) Tests that adequately take into account the individual, aggregate, and cumulative effects of environmental conditions expected in service that could possibly affect the effective con-

- tainment of strontium-90, such as absolute pressure and water immersion.
- (2) Inspection for evidence of physical damage, containment failure, or for loss of strontium-90 after each stage of testing, using methods of inspection adequate to determine compliance with the following criteria for defective: A leak resulting in a loss of 0.1 percent or more of the original amount of strontium-90 from the device and any other criteria specified in the license issued under § 32.61.
- (e) No person licensed under §32.61 shall transfer to persons generally licensed under §31.10 of this chapter, or under an equivalent general license of an Agreement State:
- (1) Any ice detection device containing strontium-90 tested and found defective under the criteria specified in a license issued under §32.61, unless the defective ice detection device has been repaired or reworked, retested, and determined by an independent inspector to meet the applicable acceptance criteria: or
- (2) Any ice detection device containing strontium-90 contained within any lot that has been sampled and rejected as a result of the procedures in paragraph (c)(2) of this section, unless:
- (i) A procedure for defining sub-lot size, independence, and additional testing procedures is contained in the license issued under §32.61; and
- (ii) Each individual sub-lot is sampled, tested, and accepted in accordance with paragraphs (c)(2) and (e)(2)(i) of this section and any other criteria as may be required as a condition of the license issued under §32.61.

[30 FR 9905, Aug. 10, 1965, as amended at 39 FR 22130, June 20, 1974; 39 FR 26397, July 19, 1974; 43 FR 6923, Feb. 17, 1978; 77 FR 43694, July 25, 2012]

§ 32.71 Manufacture and distribution of byproduct material for certain in vitro clinical or laboratory testing under general license.

An application for a specific license to manufacturer or distribute byproduct material for use under the general license of §31.11 of this chapter will be approved if:

(a) The applicant satisfies the general requirements specified in §30.33 of this chapter.